

lxqt-config

LXQt system configuration.

runtime dependencies	libXcursor (Graphic libraries/X11R7 Applications)
	qt5svg (Graphic libraries and applications/Other GUIs)
	hicolor-icon-theme (Fonts, cursors, icons, sounds and themes/Icon)
	liblxqt
make dependencies	libkscreen
	qt5tools
	lxqt-build-tools
	xf86-input-libinput

```

mkdir /data/buildroot/package/lxqt-config
cat > /data/buildroot/package/lxqt-config/Config.in<< 'EOF'
config BR2_PACKAGE_LXQT_CONFIG
    bool "lxqt-config"
    depends on BR2_PACKAGE_LIBLXQT
    depends on BR2_PACKAGE_LIBKSCREEN
    depends on BR2_PACKAGE_XLIB_LIBXCURSOR
    depends on BR2_PACKAGE_QT5SVG
    depends on BR2_PACKAGE_HICOLOR_ICON_THEME
    depends on BR2_PACKAGE_XDRIVER_XF86_INPUT_LIBINPUT
    depends on BR2_PACKAGE_QT5TOOLS
    help
        LXQt system configuration.
EOF

cat > /data/buildroot/package/lxqt-config/lxqt-config.mk<< 'EOF'
#####
#
# lxqt-config
#https://github.com/lxqt/lxqt-config/archive/refs/tags/1.1.0.tar.gz
#####
LXQT_CONFIG_VERSION = 1.1.0
LXQT_CONFIG_SOURCE = $(LXQT_CONFIG_VERSION).tar.gz
LXQT_CONFIG_SITE = https://github.com/lxqt/lxqt-config/archive/refs/tags

LXQT_CONFIG_DEPENDENCIES = liblxqt libkscreen xlib_libXcursor qt5svg
hicolor-icon-theme xdriver_xf86-input-libinput qt5tools
LXQT_CONFIG_INSTALL_TARGET = YES
LXQT_CONFIG_SUPPORTS_IN_SOURCE_BUILD = NO
LXQT_CONFIG_CONF_OPTS = -
DCMAKE_TOOLCHAIN_FILE=$(HOST_DIR)/share/buildroot/toolchainfile.cmake \
-Dlxqt_DIR=$(TARGET_DIR)/usr/share/cmake/lxqt \
-DQt5Xdg_DIR=$(TARGET_DIR)/usr/share/cmake/qt5xdg \
-DQt5XdgIconLoader_DIR=$(TARGET_DIR)/usr/share/cmake/qt5xdgiconloader \
-DKF5WindowSystem_DIR=$(TARGET_DIR)/usr/lib/cmake/KF5WindowSystem \

```

```
-DKF5Screen_DIR=$(TARGET_DIR)/usr/lib/cmake/KF5Screen \  
-Dlxqt-build-tools_DIR=$(TARGET_DIR)/usr/share/cmake/lxqt-build-tools \  
-Dfm-qt_DIR=$(TARGET_DIR)/usr/share/cmake/fm-qt \  
-DWITH_BRIGHTNESS=off \  
-DWITH_TOUCHPAD=off \  
-DCMAKE_INSTALL_PREFIX=/usr  
  
define LXQT_CONFIG_CONFIGURE_CMDS  
  if [[ ! -L "$(HOST_DIR)/usr/lib/libpcre.so.3" ]]; then ln -s  
$(HOST_DIR)/usr/lib/libpcre.so $(HOST_DIR)/usr/lib/libpcre.so.3; fi  
  if [[ ! -d @$D/buildroot-build ]]; then mkdir @$D/buildroot-build; fi  
  cd @$D/buildroot-build && \  
  export XCB_INCLUDE_DIR="$(TARGET_DIR)/usr/lib" && \  
  LDFLAGS="$(LDFLAGS) -pthread -Wl,--as-needed -Wl,--allow-shlib-undefined"  
  cmake "$D/" $(LXQT_CONFIG_CONF_OPTS)  
endef  
  
$(eval $(cmake-package))  
EOF  
  
sed -i '/menu "Custom packages"/a source "package/lxqt-config/Config.in"  
/data/buildroot/package/Config.in
```

From:

<http://www.ouarte.garden/> - **dwndoc**

Permanent link:

<http://www.ouarte.garden/doku.php?id=buildroot:lxqt-config>

Last update: **2025/02/19 10:59**

