

lxqt-connman-applet

LXQt system-tray applet for ConnMan



Paquet obsolète plus maintenu

runtime dependencies	qt5svg (Graphic libraries and applications/Other GUIs)
	connman (Networking applications)
	liblxqt
make dependencies	qt5tools
	lxqt-build-tools

```
mkdir /data/buildroot/package/lxqt-connman-applet
cat > /data/buildroot/package/lxqt-connman-applet/Config.in<< 'EOF'
config BR2_PACKAGE_LXQT_CONNMAN_APPLET
    bool "lxqt-connman-applet"
    depends on BR2_PACKAGE_QT5SVG
    depends on BR2_PACKAGE_CONNMAN<
    depends on BR2_PACKAGE_LIBLXQT
    depends on BR2_PACKAGE_QT5TOOLS
    help
        LXQt system-tray applet for ConnMan
EOF

cat > /data/buildroot/package/lxqt-connman-applet/lxqt-connman-applet.mk<<
'EOF'
#####
#
# lxqt-connman-applet
https://github.com/lxqt/lxqt-connman-applet.git
#https://git.pantherx.org/mirror/lxqt/lxqt-connman-applet/-/archive/master/l
xqt-connman-applet-master.tar.gz
#####
LXQT_CONNMAN_APPLET_VERSION = master
LXQT_CONNMAN_APPLET_SOURCE = lxqt-connman-applet-master.tar.gz
LXQT_CONNMAN_APPLET_SITE =
https://git.pantherx.org/mirror/lxqt/lxqt-connman-applet/-/archive/master

LXQT_CONNMAN_APPLET_DEPENDENCIES = qt5svg connman liblxqt qt5tools
LXQT_CONNMAN_APPLET_INSTALL_TARGET = YES
LXQT_CONNMAN_APPLET_SUPPORTS_IN_SOURCE_BUILD = NO
LXQT_CONNMAN_APPLET_CONF_OPTS = -
DCMAKE_TOOLCHAIN_FILE=$(HOST_DIR)/share/buildroot/toolchainfile.cmake \
-Dlxqt_DIR=$(TARGET_DIR)/usr/share/cmake/lxqt \
-DQt5Xdg_DIR=$(TARGET_DIR)/usr/share/cmake/qt5xdg \
-DQt5XdgIconLoader_DIR=$(TARGET_DIR)/usr/share/cmake/qt5xdgiconloader \
```

```
-DKF5WindowSystem_DIR=$(TARGET_DIR)/usr/lib/cmake/KF5WindowSystem \  
-Dlxqt-build-tools_DIR=$(TARGET_DIR)/usr/share/cmake/lxqt-build-tools \  
-DCMAKE_INSTALL_PREFIX=/usr
```

```
define LXQT_CONNMAN_APPLET_CONFIGURE_CMDS  
  rm -rf $(@D)/  
  git clone https://github.com/lxqt/lxqt-connman-applet.git $(@D)  
  if [[ ! -L "$(HOST_DIR)/usr/lib/libpcre.so.3" ]]; then ln -s  
$(HOST_DIR)/usr/lib/libpcre.so $(HOST_DIR)/usr/lib/libpcre.so.3; fi  
  if [[ ! -d $(@D)/buildroot-build ]]; then mkdir $(@D)/buildroot-build; fi  
  cd $(@D)/buildroot-build && \  
  LDFLAGS="$(LDFLAGS) -pthread -Wl,--as-needed -Wl,--allow-shlib-undefined"  
  cmake "$(@D)/" $(LXQT_CONNMAN_APPLET_CONF_OPTS)  
endef  
  
$(eval $(cmake-package))  
EOF
```

```
sed -i '/menu "Custom packages"/a source "package/lxqt-connman-  
applet/Config.in"' /data/buildroot/package/Config.in
```

From:

<http://www.ouarte.garden/> - **dwndoc**

Permanent link:

<http://www.ouarte.garden/doku.php?id=buildroot:lxqt-connman-applet>

Last update: **2025/02/19 10:59**

