

lxqt-notificationd

LXQt notification daemon and library.

runtime dependencies	qt5base (Graphic libraries and applications/Other GUIs)
	kwindowsystem
	liblxqt
make dependencies	lxqt-build-tools
	qt5tools

```
mkdir /data/buildroot/package/lxqt-notificationd
cat > /data/buildroot/package/lxqt-notificationd/Config.in<< 'EOF'
config BR2_PACKAGE_LXQT_NOTIFICATIOND
    bool "lxqt-notificationd"
    depends on BR2_PACKAGE_QT5
    depends on BR2_PACKAGE_LIBLXQT
    depends on BR2_PACKAGE_KWINDOWSYSTEM
    depends on BR2_PACKAGE_QT5TOOLS
    help
        LXQt notification daemon and library.
EOF

cat > /data/buildroot/package/lxqt-notificationd/lxqt-notificationd.mk<<
'EOF'
#####
#
# lxqt-notificationd
#https://github.com/lxqt/lxqt-notificationd/archive/refs/tags/1.1.0.tar.gz
#####
LXQT_NOTIFICATIOND_VERSION = 1.1.0
LXQT_NOTIFICATIOND_SOURCE = $(LXQT_NOTIFICATIOND_VERSION).tar.gz
LXQT_NOTIFICATIOND_SITE =
https://github.com/lxqt/lxqt-notificationd/archive/refs/tags

LXQT_NOTIFICATIOND_DEPENDENCIES = qt5base liblxqt kwindowsystem qt5tools
LXQT_NOTIFICATIOND_INSTALL_TARGET = YES
LXQT_NOTIFICATIOND_SUPPORTS_IN_SOURCE_BUILD = NO
LXQT_NOTIFICATIOND_CONF_OPTS = -
DCMAKE_TOOLCHAIN_FILE=$(HOST_DIR)/share/buildroot/toolchainfile.cmake \
-Dlxqt_DIR=$(TARGET_DIR)/usr/share/cmake/lxqt \
-DQt5Xdg_DIR=$(TARGET_DIR)/usr/share/cmake/qt5xdg \
-DQt5XdgIconLoader_DIR=$(TARGET_DIR)/usr/share/cmake/qt5xdgiconloader \
-DKF5WindowSystem_DIR=$(TARGET_DIR)/usr/lib/cmake/KF5WindowSystem \
-Dlxqt-build-tools_DIR=$(TARGET_DIR)/usr/share/cmake/lxqt-build-tools \
-Dfm-qt_DIR=$(TARGET_DIR)/usr/share/cmake/fm-qt \
-DCMAKE_INSTALL_PREFIX=/usr
define LXQT_NOTIFICATIOND_CONFIGURE_CMDS
    if [[ ! -L "$(HOST_DIR)/usr/lib/libpcre.so.3" ]]; then ln -s
$(HOST_DIR)/usr/lib/libpcre.so $(HOST_DIR)/usr/lib/libpcre.so.3; fi
```

```
if [[ ! -d $(@D)/buildroot-build ]]; then mkdir $(@D)/buildroot-build; fi
cd $(@D)/buildroot-build && \
  LDFLAGS="$(LDFLAGS) -pthread -Wl,--as-needed -Wl,--allow-shlib-undefined"
cmake "$(@D)/" $(LXQT_NOTIFICATIOND_CONF_OPTS)
endif

$(eval $(cmake-package))
EOF

sed -i '/menu "Custom packages"/a source "package/lxqt-
notificationd/Config.in"' /data/buildroot/package/Config.in
```

From:

<http://www.ouarte.garden/> - **dwndoc**

Permanent link:

<http://www.ouarte.garden/doku.php?id=buildroot:lxqt-notificationd>

Last update: **2025/02/19 10:59**

