

lxqt-runner

The LXQt application launcher

runtime dependencies	kwindowssystem
	lxqt-globalkeys
	muparser
make dependencies	qt5tools
	lxqt-build-tools

```
mkdir /data/buildroot/package/lxqt-runner
cat > /data/buildroot/package/lxqt-runner/Config.in<< 'EOF'
config BR2_PACKAGE_LXQT_RUNNER
    bool "lxqt-runner"
    depends on BR2_PACKAGE_KWINDOWSYSTEM
    depends on BR2_PACKAGE_LXQT_GLOBALKEYS
    depends on BR2_PACKAGE_MUPARSER
    depends on BR2_PACKAGE_QT5TOOLS
    help
        The LXQt application launcher
EOF

cat > /data/buildroot/package/lxqt-runner/lxqt-runner.mk<< 'EOF'
#####
#
# lxqt-runner
#https://github.com/lxqt/lxqt-runner/archive/refs/tags/1.1.0.tar.gz
#####
LXQT_RUNNER_VERSION = 1.1.0
LXQT_RUNNER_SOURCE  = $(LXQT_RUNNER_VERSION).tar.gz
LXQT_RUNNER_SITE    = https://github.com/lxqt/lxqt-runner/archive/refs/tags

LXQT_RUNNER_DEPENDENCIES = kwindowssystem lxqt-globalkeys muparser qt5tools
LXQT_RUNNER_INSTALL_TARGET = YES
LXQT_RUNNER_SUPPORTS_IN_SOURCE_BUILD = NO
LXQT_RUNNER_CONF_ENV = PKG_CONFIG_PATH=$(TARGET_DIR)/usr/local/lib/pkgconfig
LXQT_RUNNER_CONF_OPTS = -
DCMAKE_TOOLCHAIN_FILE=$(HOST_DIR)/share/buildroot/toolchainfile.cmake \
-Dlxqt_DIR=$(TARGET_DIR)/usr/share/cmake/lxqt \
-DQt5Xdg_DIR=$(TARGET_DIR)/usr/share/cmake/qt5xdg \
-DQt5XdgIconLoader_DIR=$(TARGET_DIR)/usr/share/cmake/qt5xdgiconloader \
-DKF5WindowSystem_DIR=$(TARGET_DIR)/usr/lib/cmake/KF5WindowSystem \
-Dlxqt-build-tools_DIR=$(TARGET_DIR)/usr/share/cmake/lxqt-build-tools \
-Dlxqt-globalkeys_DIR=$(TARGET_DIR)/usr/share/cmake/lxqt-globalkeys \
-Dlxqt-globalkeys-ui_DIR=$(TARGET_DIR)/usr/share/cmake/lxqt-globalkeys-
ui \
-DCMAKE_INSTALL_PREFIX=/usr

define LXQT_RUNNER_CONFIGURE_CMDS
```

```
if [[ ! -L "$(HOST_DIR)/usr/lib/libpcre.so.3" ]]; then ln -s
$(HOST_DIR)/usr/lib/libpcre.so $(HOST_DIR)/usr/lib/libpcre.so.3; fi
if [[ ! -d "$@"/buildroot-build ]]; then mkdir "$@"/buildroot-build; fi
cd "$@"/buildroot-build && \
PKG_CONFIG_PATH=$(TARGET_DIR)/usr/local/lib/pkgconfig LDFLAGS="$(LDFLAGS)
-pthread -Wl,--as-needed -Wl,--allow-shlib-undefined" cmake "$@"/"
$(LXQT_RUNNER_CONF_OPTS)
endif

$(eval $(cmake-package))
EOF

sed -i '/menu "Custom packages"/a source "package/lxqt-runner/Config.in"'
/data/buildroot/package/Config.in
```

From:
<http://www.ouarte.garden/> - **dwndoc**

Permanent link:
<http://www.ouarte.garden/doku.php?id=buildroot:lxqt-runner>

Last update: **2025/02/19 10:59**

