

# lxqt-wallet

Secure storage of information for lxqt

|                             |   |
|-----------------------------|---|
| <b>runtime dependencies</b> | libgcrypt (Libraries/Crypto)<br>libsecret |
| <b>make dependencies</b>    | qt5<br>kwallet<br>libsecret<br>qt5tools   |

```
mkdir /data/buildroot/package/lxqt-wallet
cat > /data/buildroot/package/lxqt-wallet/Config.in<< 'EOF'
config BR2_PACKAGE_LXQT_WALLET
    bool "lxqt-wallet"
    depends on BR2_PACKAGE_LIBGCRYPT
    depends on BR2_PACKAGE_LIBSECRET
    depends on BR2_PACKAGE_QT5TOOLS
    help
        Secure storage of information for lxqt
EOF

cat > /data/buildroot/package/lxqt-wallet/lxqt-wallet.mk<< 'EOF'
#####
#
# lxqt-wallet
#https://github.com/lxqt/lxqt_wallet/archive/refs/tags/3.2.2.tar.gz
#####
LXQT_WALLET_VERSION = 3.2.2
LXQT_WALLET_SOURCE = $(LXQT_WALLET_VERSION).tar.gz
LXQT_WALLET_SITE = https://github.com/lxqt/lxqt_wallet/archive/refs/tags

LXQT_WALLET_DEPENDENCIES = libgcrypt libsecret qt5tools
LXQT_WALLET_INSTALL_TARGET = YES
LXQT_WALLET_SUPPORTS_IN_SOURCE_BUILD = NO
LXQT_WALLET_CONF_OPTS = -
DCMAKE_TOOLCHAIN_FILE=$(HOST_DIR)/share/buildroot/toolchainfile.cmake \
    -DCMAKE_INSTALL_PREFIX=/usr

define LXQT_WALLET_CONFIGURE_CMDS
    if [[ ! -L "$(HOST_DIR)/usr/lib/libpcre.so.3" ]]; then ln -s
$(HOST_DIR)/usr/lib/libpcre.so $(HOST_DIR)/usr/lib/libpcre.so.3; fi
    if [[ ! -d $(@D)/buildroot-build ]]; then mkdir $(@D)/buildroot-build; fi
    cd $(@D)/buildroot-build && \
        LDFLAGS="$(LDFLAGS) -pthread -Wl,--as-needed -Wl,--allow-shlib-undefined"
    cmake "$(@D)/" $(LXQT_WALLET_CONF_OPTS)
endef

$(eval $(cmake-package))
```

EOF

```
sed -i '/menu "Custom packages"/a source "package/lxqt-wallet/Config.in" '/data/buildroot/package/Config.in
```

From:

<http://www.ouarte.garden/> - **dwndoc**

Permanent link:

<http://www.ouarte.garden/doku.php?id=buildroot:lxqt-wallet>

Last update: **2025/02/19 10:59**

