marked

A markdown parser built for speed

runtime dependencies	nodejs-git
make dependencies	npm

```
mkdir /data/buildroot/package/marked
cat > /data/buildroot/package/marked/Config.in<< 'EOF'
config BR2_PACKAGE_MARKED
        bool "marked"
        depends on BR2_PACKAGE_NODEJS_GIT
        help
          A markdown parser built for speed
EOF

cat > /data/buildroot/package/marked/marked.mk<< 'EOF'
################################################################
#
# marked
# https://github.com/markedjs/marked/archive/refs/tags/v4.0.12.tar.gz
#
################################################################
MARKED_VERSION = 4.0.12
MARKED_SOURCE  = v$(MARKED_VERSION).tar.gz
MARKED_SITE    = https://github.com/markedjs/marked/archive/refs/tags

MARKED_DEPENDENCIES = nodejs

define MARKED_INSTALL_TARGET_CMDS
  npm install -g --prefix "$(TARGET-DIR)"/usr "$(@D)"/marked-
$(MARKED_VERSION).tgz
  install -d "$(TARGET-DIR)"/usr/share/licenses/marked
  ln -s ../../../lib/node_modules/marked/LICENSE "$(TARGET-
DIR)"/usr/share/licenses/marked/LICENSE
endef

$(eval $(generic-package))
EOF

sed -i '/menu "Custom packages"/a source "package/marked/Config.in"'
/data/buildroot/package/Config.in
```

From:

<http://www.ouarte.garden/> - **dwndoc**

Permanent link:

http://www.ouarte.garden/doku.php?id=buildroot:marked

Last update: **2025/02/19 10:59**