

qt5-translations

A cross-platform application and UI framework (Translations)

runtime dependencies	qt5base (Graphic libraries and applications/Other GUIs)
	qt5tools (Graphic libraries and applications/Other GUIs)

```
mkdir /data/buildroot/package/qt5-translations
cat > /data/buildroot/package/qt5-translations/Config.in<< 'EOF'
config BR2_PACKAGE_QT5_TRANSLATIONS
    bool "qt5-translations"
    depends on BR2_PACKAGE_QT5BASE
    depends on BR2_PACKAGE_QT5TOOLS
    help
        A cross-platform application and UI framework (Translations)
EOF

cat > /data/buildroot/package/qt5-translations/qt5-translations.mk<< 'EOF'
#####
#
# qt5-translations
#https://github.com/qt/qttranslations/archive/refs/tags/v5.15.5-lts-lgpl.tar
.gz
#####
QT5_TRANSLATIONS_VERSION = 5.15.5
QT5_TRANSLATIONS_SOURCE = v$(QT5_TRANSLATIONS_VERSION)-lts-lgpl.tar.gz
QT5_TRANSLATIONS_SITE =
https://github.com/qt/qttranslations/archive/refs/tags

QT5_TRANSLATIONS_DEPENDENCIES = qt5base qt5tools
QT5_TRANSLATIONS_BIN_ARCH_EXCLUDE = /usr/lib

define QT5_TRANSLATIONS_BUILD_CMDS
    mkdir -p $(@D)/build
    cd "$(@D)/build" && \
    qmake "../" && \
    make
endef

define QT5_TRANSLATIONS_INSTALL_TARGET_CMDS
    cd $(@D)/build && \
    make INSTALL_ROOT="${TARGET_DIR}" install
    mkdir -p "${TARGET_DIR}"/usr/share/licenses/qt5-translations
    install -D -m644 $(@D)/LICENSE.* "${TARGET_DIR}"/usr/share/licenses/qt5-
translations/
endef

$(eval $(generic-package))
EOF
```

```
sed -i '/menu "Custom packages"/a source "package/qt5-  
translations/Config.in"' /data/buildroot/package/Config.in
```

From:

<http://www.ouarte.garden/> - **dwndoc**

Permanent link:

<http://www.ouarte.garden/doku.php?id=buildroot:qt5-translations>

Last update: **2025/02/19 10:59**

